

## AFTER CARE

To maintain the appearance of this tap, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild liquid detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Abrasive cleaners, scouring cleaners and acid cleaners **must not be used** under any circumstances. All bath cleaning powders and liquids will damage the surface of your fitting even the non-scratch cleaners.

Avoid contact with all solvents and any harsh household chemicals. You will damage the plated finish and void your guarantee.

## GUARANTEE AND LIABILITY

In the unlikely event that you should experience any defect in the material or workmanship of your mixer tap within 5 years of purchase, we will replace the faulty part free of charge. Decorative surface finishes are guaranteed for one year from the date of purchase provided that our advise concerning care has been observed and no scouring agents have been used. This is provided that the mixer or tap has been used for normal domestic purposes in the UK and that the care, installation and maintenance instructions have been observed.

Scuff and scratches caused by normal wear and tear, improper installation or accidental damage are excluded from this guarantee.

You should retain a copy of your dated invoice as proof of purchase to validate any claims under this guarantee.

No other warranties, express or implied, are made, including merchantability or fitness for a particular purpose.



Please Keep Me Safe


## Spare Parts and Service



Contact: Sterling  
Phone: 01684 299555  
Fax: 01684 290958  
Email: [sales@sterling.eu.com](mailto:sales@sterling.eu.com)  
Website: [www.sterling.eu.com](http://www.sterling.eu.com)

## MIRA

**clearwater**<sup>®</sup>  
THE CLEAR CHOICE



## Fitting Instructions and Parts List


Please read these instructions before you install and use the tap, be sure to keep them safe for future reference and to request replacement parts.

All designs, descriptions and dimensions are subject to change without notice.

## PARTS LIST

### MIRA

Ref. MI2SS



In the unlikely event you find a part missing please contact our Customer Service Helpline on 01684 299555 for immediate despatch of part.

## MAINTENANCE

### IF THE FITTING BEGINS TO DRIP

- 1 Turn off the water supply
- 2 Loosen grub screw under handle lever, remove handle and valve
- 3 Carefully clean seating, rubber washer and ceramic disc
- 4 Replace valve and handle, then turn on the water supply
- 5 If problem persists contact our helpline quoting the product code

Where an aerator is fitted to the outlet of the spout, it will need occasional cleaning. This will be evident when the water flow slows down to an unacceptable level. To accomplish this unscrew the outlet in an anti-clockwise direction and remove the mesh. Immerse the mesh in a suitable descaling fluid overnight, rinse thoroughly in clean water and re-install.

## REMEMBER

Minimum water supply pressure **0.3 bar**.

Do not exceed the flow rate stated on your filter.

If water pressure causes the flow rate to exceed 4 litres per minute, damage to the tap can result. A pressure reducing valve must be fitted.

**It is very important that you read through the following instructions BEFORE you install and use the tap.**

## PREPARATION

We strongly recommend installing particle filters and isolation valves to both hot and cold feeds. This will help to prevent premature failure of valves and make any future maintenance easier.

Flush the plumbing system before installing the mixer tap. This is to void plumbing residues clogging the mesh of the aerated outlet, or possibly damaging the valve's washers. This is especially important where extensive plumbing work has been carried out.

First shut off your water heating system then, with your mains stop cock closed, open the lowest hot and cold taps in the house and allow to run until the cold storage tank and pipes are empty. (The hot water storage cylinder always remains full).

## INSTALLATION

- Roll the smallest round black o-ring (R008) on the part threaded rod (L2A310N) where the thread is narrower. Screw the threaded rod (L2A310N) into the tap base hand tight.
- Insert the stainless steel base ring and seal onto the threaded rod and place through the tap hole (20-35mm hole size) so it can seal once tightened.
- Attached the rubber seal (D1R048N) and metal disc (D1A310N) up the thread rod. Then attached the nut (L3A327N) and tighten making sure the tap is in the desired position before fully tightening.
- Push the second smaller black rubber seal D1R047N into part 22 and screw it to the base on the threaded rod.
- Push the clear into the plastic speed fit L9S29N and screw it to part 22. Then insert the 1/4" white tubing.
- Use the 3 way tee with shut off lever to spur off the cold water mains pipe, attach the john guest 3/8" to 1/4" bsp connector (Ci320816FS) to the Tee (27916).
- Install the twist lock head to the cupboard carcass leaving adequate room to remove the filter.
- Install the twist lock cartridge.
- Cut 1/4" tube into two pieces, adequate so that it reaches your filter head. Simply push the tubes into the filter head holding the little tab back. Do the same for the connection into the Speedfit.
- Having first checked all the new connections, turn on the mains stop cock, close all taps except the new filter tap and as the system starts to refill check for leaks.

### FOR BEST RESULTS

Run off around 5 litres of water from the filter line prior to drinking. Reduce the filter water flow to around 2 litres per minute by adjusting the 3 way tee shut off valve (27916). This will maximise the filter contact time and lifespan. The filter must be changed at least every 12 months. We suggest changing the cartridge every 6 months in normal household usage (filter life 4000 litres usage).

### USING OTHER FILTERS/WATER SOFTENING SYSTEMS

Make sure that the filter line isn't over pressurised, as this filter line is only design for a maximum of 4 litres per minute and may fail if over pressurised. Install a pressure reducing valve in such instances of very high pressure.

### OTHER

Remember to fill in and send off your free post warranty form.